



CP-10

AUTOMATIC CAPPING MACHINE



SPECIFICATIONS

| | |
|--------------------|----------------------------------|
| Model | CP-10 |
| Electrical Supply | 220VAC 50/60Hz Single Phase |
| Power Consumption | 700 W |
| Capping Head | 1 Capping head |
| Bottle Size Range | Dia. 20mm ~ Dia. 100mm |
| Bottle Height | 300mm Max. |
| Cap Size Range | Dia. 20mm ~ Dia.40mm |
| Conveyor Width | 114mm |
| Conveyor Direction | Left to right/ Right to left |
| Air Pressure | 4 Kgs |
| Dimension | 2000mm(L) x 980mm(W) x 1840mm(H) |
| Net Weight | Approx. 150 Kgs |



OPTIONAL

- CE Specification Set, included Safety Module
- Automatic Cap feeding system
- 1000mm Feeding Turn Table
- 1000mm Collection Turn Table



FEATURE

- Integrated digital control with Panasonic PLC and Delta colored HMI controls for easy operation.
- Calculates and displays the production rate (Bottles/Minute)
- Capping zone protected by interlock guards for safety registration
- Bottle gating system to accurately locate bottles under capping station.
- Capping head controlled by torque motor.
- Designed for easy change-over and cleaning.
- Bottle capped quantity count function – Automatically calculate the quantity of capped product, via large display can also view current capped quantity in order to keep record and monitoring the production
- Sturdy conveyor system driven by Siemens motor. Adjustable conveyor guide rails to accommodate with different products.
- Flexible enough to handle production schedule and product changes quickly and simply
- Memory slots for storing capping parameters for future operation
- Easy to install and operate, it only requires minimum maintenance for maximum performance and a long machine life time.
- Perfect inline connection with FL-12 & FL-14 automatic filling machine.

